•••

CEX – 10.1" Industrial Flat Panel Monitor







Features

- •• 10.1" SVGA TFT LCD Panel support 1920 x 1200 pixels
- 6mm Aluminum front bezel with strengthen glass
- Rugged construction design
- •• Input signal: VGA (15 Pin D-sub), HDMI
- 400 cd/m2 brightness
- IP65 Rate front panel
- OSD control keys to optimize the display
- AC 100-240V wide range external ac adapter
- •• NEMA4 / IP 65 compliant front panel (optional)

Specifications

LCD Panel	Display Type: 10.1" SVGA TFT LCD
	Resolution: 1920 x 1200
	Max. color: 262,144 colors
	Luminance: 400 cd/m2
	View Angle: 110°(H), 80°(V)
	Pixel Pitch: 0.1695 x 0.1695 mm
	Contract ratio: 800:1
	Response Time: 5 ms
	Power Consumption: 4 W
	LED MTBF: 50,000hrs
Signal input	VGA (15 pin D-sub connector), HDMI
Protect glass	3 mm strengthen glass
OSD	Brightness, Contrast, H/V Position, Color, Phase, Clock, auto
	tune and recall
Touch Screen (optional)	Internal USB or RS-232 interface controller
	Type: Analog resistive type: 25VDC ≥ 20MΩ
	Resolution: continuous
	Light transmission: 80% or more
	Power consumption: <5V @ 1mA
	Surface hardness: 3H
	Operating force: ≤100g
	Life expectancy: 35 million
	Operation system: Windows 7/8/XP/NT/CE, DOS, Linux
Power Supply	Input: 100~240VAC, 50/60Hz
	Output: DC12V @ 4A/48W, external ac adapter
Construction	Heavy duty steel and aluminum front panel
Environment	Operating temperature: 32 °F~113 °F (0 °C to 45°C)
	Storage temperature: -4 °F~140 °F (-20 °C to 60° C)
	Storage humidity: 5% to 95% @ 40°C, on-condensing
	Vibration: 10 ~ 150Hz, 0.15mm 10 cycles 1G
	Shock: 30G peak acceleration (11 msec. duration)
Safety	CE/FCC/Rohs
Dimension WxHxD (mm)	Dimensions: 274 x 193 x 34mm
	Packing dimension: 423 x 365 x 184mm
Weight (kgs)	NET weight: 1.5KG , Gross weight: 2.8KG

Computer Express, LLC