

CEX – 7” HMI Industrial Panel PC’s

IPPC-A7000T



• Features

- 7” industrial (HMI) touch panel pc running WIN CE6.0
- ARM mother board with Cortex A8 1.0 GHz
- Memory: 512M Bytes DDR2 SDRAM + storage device 256M flash
- Plastic case and fan less design
- 7” resistive / projective capacitive touch screen

• Specifications

| | |
|--------------------------|---|
| CPU | Cortex A8 1.0GHz |
| Display | 7" high-brightness LCD screen; 250cd/m2 brightness |
| Resolution | 800 x 480 |
| Memory | DDRII 512MB |
| Flash | 256 flash |
| Extension storage | Micro SD, Max up to 32GB |
| Network interface | 1x 100Mbps Ethernet controller |
| I/O | <ul style="list-style-type: none"> • 2 x RS232 COM, 1 x RS232 (test port) • 1 x RS485 com • 3 x USB2.0 + (1 x USB slave) • 1 x LAN • Support 19V ~ 24V Power input |
| Touch Screen | Resistive / projected capacitive touch screen (optional) |
| Power Supply | Supports 9-24VDC. Kindly advise 24VDC or 12VDC |
| Power consumption | 3.5W |
| Watchdog | The time can be adjusted |
| buzzer | Built-in, provides function control sound; |
| WIFI | Optional |
| Operating system | WIN CE6.0 |
| Fan less | Fan less design |
| Dimension | 192.5mm (L) x 128.5mm (W) x 26.2mm (H) |
| Installation | Panel type, wall- mount, Table, bracket etc |
| Net weight | 0.5kg |
| Gross weight | About 2kg |
| Operating Temp | -10°C~60°C |
| Humidity | -20°C~70°C |