

CEX – IP KVM-1500M series

8ports/16ports 1U rack mount 15" LED KVM drawer over IP



Features

- KVM (Keyboard, video, mouse) access over IP and analogous telephone line (modem needed)
- Full control under any OS, in BIOS mode, during boot at blue screen
- 256 bit SSL encryption of all transmitted data and certificate management
- Port to connect a user console for direct analogous access to KVM switch
- Can be used with most standard KVM
- To switch the host computer through the hotkey or OSD menu, which can manage up to 512 computers
- Password security protection, only authorized users can view and manage on-line computer
- Support a variety of brand industrial computer and the server EVOC/Lenovo/IBM/DELL/HP/SUN, etc.
- Support various operating system: Microsoft, Linux, Unix, etc.

Specifications

Model	IP KVM-1508M	IP KVM-1516M
Computer connect	Direct: 8	Direct: 16
	Max: 256	Max: 512
Connector Port	8 / 16 x HDB-15 female (Yellow)	
IP Module console	1 x RJ45 port, 1 x VGA port (male), 1 x USB	
Selection connection	Support daisy-chained serial connection (8 levels) and stacking cascade connection (2 levels)	
Keyboard	104 Mechanical mute keyboard	
Mouse	Touchpad	
Switch Mode	Hotkey, OSD Menu	
Auto scanning interval	5-99 second	
Power input	DC12V input , (AC100-240V 47-63HHz, 35W) optional	
LED indicator	Power Indicator	2
	Selection indicator	16
	Boost on-line indicator	16
	Num lock	1
	Caps lock	1
	Scroll lock	1
Work Environment	Operating Temperature	-10°C ~60°C
	Storage Temperature	-20°C ~70°C
	Humidity	0%-95%RH
Cabinet Material	High-strength and anti-corrosive steel plate	
Color	Insulated black (optional)	
For Cabinet	800-1040mm	
Net weight	12KG-16KG	
Gross weight	16KG-20KG	
Dimension (L x W x H)	520mm*480.4mm*44mm	
Package (L x W x H)	708mm*608mm*195mm	
Certificate	CE, FCC, ROHS	